

HF-100[®]

FIVE EASY STEPS

HF-100 Grip Tape Activator



1



2



3



4



5

HF-100[®] Grip Tape Activator

Follow These Steps in removal of your grip

Secure the club in a vise using a rubber clamp. Not too tight on graphite shafts.

Remove the old grip using retractable razor knife with a **“hooked blade”**. Using the hooked blade razor knife stand to one side of the vise then place both hands on the knife. Be careful on graphite shafts not to angle the blade downward as you will mar the shaft. Try to keep the blade parallel to the shaft during the cutting motion. Do not use a straight razor blade as it can very easily slip and slice a finger.

Strip off the old grip and peel any remaining tape.

1. Apply 9 inches of new two side grip tape extending it a 1/4 inch beyond the butt end of the shaft. Then twist and fold the remaining tape into the end of the shaft making sure no edges of the shaft are exposed; as this will grab the grip and make it difficult to install. *
2. While wearing **SAFETY GLASSES**, spray a small amount of HF-100 the entire length of the tape.
3. Spray a small amount inside the grip.
4. Install the grip by pushing it over the taped end of the shaft, hold a paper towel at the butt end of the grip. This will eliminate any excess grip solution squirting on your clothes or face.
5. After you have installed the grip wipe any further fluid from the shaft using the same paper towel. Then gently tap the butt end of the grip on the ground to force out any trapped fluid. If the correct amount of fluid is used the club should be ready to play in 10-15 minutes.

*Note: When applying a grip strip make sure you remove both liners exposing the adhesive. There is scoring line on one side of the liner which makes it easy to remove. Place the adhesive side onto the golf shaft and wrap the tape around the shaft with the other liner still attached. When strip is completely wrapped around the shaft remove the remaining liner.



Brampton[®]

TECHNOLOGY LTD.